

# GORI

- THE SCANDINAVIAN WOODCARE EXPERTS

## GORI 51

High Traffic Floor Finish **WATER BASED**



Distributed by: **Dougall Flooring Limited**

**SHOWROOM:**

Shop 1B, Dragon Centre Plaza  
6 South Avenue  
Kingston 10, Jamaica, W.I.  
Tel: (876) 926-5969, 929-0547  
Fax: (876) 920-3377 (fax)

**FACTORY:**

110A Bay Farm Road  
Kingston 11, Jamaica, W.I.  
Tel: (876) 923-8616, 923-8618  
Fax: (876) 923-8617 (fax)

 **DYRUP**



# GORI 51

## High Traffic Floor Finish

GORI 51 High Traffic Floor Finish is a clear, water based (Acrylic-polyurethane) floor finish for wooden flooring and all other interior woodwork such as handrails and stairs.

GORI 51 can also be used on cork. Use GORI 51 in areas, where high resistance to wear and detergents is required.

GORI 51 is tested according to EN71, 3 - safe to use on children's toys.

### Properties

- Hard wearing
- Almost odourless
- Dirt repellent and abrasion resistant
- Available in matt, semi-gloss and high gloss

### Use

Pre-treatment: Surfaces that have been treated before should be sanded down.

The surface must be clean and dry: remove wax, grease and dirt with a suitable detergent.

### Key Points

- Water based
- 3 coats in one day
- Touch dry in 25 minutes

### Application

Apply GORI 51 with a flat brush or roller. Previously treated surfaces: 1-2 coats. New and planed/worn down surfaces: Apply 1 coat, leave to dry and then sand with fine sandpaper. Repeat treatment of 1-2 coats of GORI 51.

Coverage: Approx. 10 m<sup>2</sup> / l, depending on the substrate.

Touch dry: 25 minutes.

Recoat: After 4 hours.

