

GORI

- THE SCANDINAVIAN WOODCARE EXPERTS

GORI 91

Opaque Woodstain

NEW



GORI 91

Opaque Woodstain

The new water based GORI 91 OPAQUE WOODSTAIN protects your wood and virtually all other bases. A bonding agent with improved formula ensures stronger bonding of paint with base, and far greater elasticity. The product forms an opaque, hard-wearing elastic film on all interior and exterior wood surfaces.

Properties

- Outdoor/Indoor
- Breathable and allows moisture to escape. Forms an elastic film
- EN71 Part 3 tested. Safe for use on children's toys once top coat has dried. Withstands effects of simulated spit and sweat in accordance with DIN 53 160, parts 1 and 2.
- Highly opaque - ideal for bold colour changes
- Decorative and weather proof

Use

Water based wood protection, which forms an opaque, hard-wearing elastic film on all interior and exterior wood surfaces. Also suitable for coating pre-treated aluminum, galvanised and primed ssteel surfaces and UPVC surfaces.

Recommended System

Surface coating system for exterior use: Untreated soft wood: 1 coat of primer (GORI 22 Wood Preserver), 2-3 coundercoats all over with GORI 91. Other woods (e.g. hardwood)

- no undercoat required: 2-3 coats of GORI 91. Renovation: On sound properly treated finishes: 1-2 coats of GORI 91. Surface coating system for interior use: 2-3 coats of GORI 91. Pretreatment of wood not required.

Key Points


- Outdoor / Indoor
- Weatherproof for up to 12 years, depending on construction and exposure.
- Application: Brush, roller or spraygun
- 1 l = approx. 10 m² depending on the type of wood and absorbency.
- Touch Dry: Approx. 6 hours
- Recoat: After approx. 12 hours (measured at 23°C and 60% relative humidity).
- Clean tools: Immediately with soap and water.

Applying Wood protection


Surface pre-treatment: Sand down badly-weathered surfaces to sound wood. Remove sawdust and any other loose material. Scrub and rinse highly resinous woods with cellulose thinner. In general wood protection can be applied with brush or spraygun:

- Brush: Apply product generously along wood grain to favour impregnation.
- Spray Gun: Maintain spray gun perpendicular to and at a constant distance from surface. Alternate direction of spray coats to ensure they overlap slightly.





Silver Grey




Bornholm Red




Corn Yellow




Moss Green



Night Black



Pigeon Blue



Snow White

GORI 91
Colourcard

Also available in the GORI range:



GORI 22
Colourless Preservative

GORI 22 is an outdoor preserver, which can be used against all dry woodboring insects, as well as termites and decay fungi. GORI 22 contains insecticide and fungicide and has a high penetration. Can be used together with all other GORI woodprotection systems.



GORI 36
Teak Oil

GORI 36 Teak oil is a natural oil, suited for exotic and tropical woods - in particular garden furniture. GORI 36 Teak Oil is water- and alcohol resistant. GORI 36 enhances the wood grain and recovers the wood's natural balance.



GORI 38
Decking Oil/Terrazas

GORI 38 Decking Oil / Terrazas is used for outdoor wooden decks - also suited for exotic wood species such as teak, nyatoh, bangkirai, meranti and ipe and also wood treated through pressure-/VAC VAC treatment. GORI 38 is water repellent, walkable, has a high penetration, and gives the wood a natural wood sheen. Available in several different shades.



GORI 44
Facades - Fascias - Fences

GORI 44 protects and decorates outdoor wooden surfaces. GORI 44 is water repellent and protects against fungi and blue stain. It will not crack or peel off and is easy to apply. Available in more than 20 different shades.



GORI 79
Colourless Woodprotection

GORI 79 is ideal for doors, windows, fences, beams and panelling. It is water repellent, has a high UV-protection and protects against fungi and bluing. The product is easy to apply, quick drying and has a low odour and high durability. When using GORI 79 there is no need to remove previous coating.



GORI 88
Windows & Doors

GORI 88 is a translucent, satin wood protection, which protects and decorates outdoor wood surfaces such as windows and doors. GORI 88 is water repellent and easy to apply. The coating will not crack or peel off. GORI 88 protects against surface fungi and blue stain. Available in more than 20 different shades.



GORI 99
Extreme - Windows & Doors

GORI 99 is ideal for windows and doors, beams, panelling etc. It has a high UV-protection, is water repellent and protects against fungi and blue stain. GORI 99 will not crack or peel off and is easy to apply. Available in more than 20 different shades.



GORI 51
High Traffic Floor Finish

GORI 51 enhances the natural glow of your floors. It can be used on all interior wooden flooring, and also on cork, stairs and handrails. GORI 51 is available in matt, semi-gloss and high gloss.



GORI 57
Marine Finish

GORI 57 Marine Finish is a clear varnish for boats and other special areas. GORI 57 can be used on all interior and exterior wood on boats - above the water line. GORI 57 has a high UV-resistance and is easy to apply. GORI 57 also protects against weather, deterioration, water, sun and heat.

www.dyrup.com

Dyrup A/S

Gladsaxevej 300

DK-2860 Søborg

Denmark

Tel: +45 39 57 93 00

Fax: +45 39 57 93 93

GORI® is a registered trademark

Copyright © Dyrup A/S - September 2009

 DYPURP